

SANDEN SD5H14 (EX SD508/510) – 12 V

Maximální konstantní/krátkodobé otáčky – 6 000/7 000 ot./min.

Směr otáčení – pravý/levý

Minimální množství oleje – 180 ml

Typ	Spojka – průměr mm	Připojení – typ víka	Vývody	Napětí V	Registr. číslo
SD5H14 – model 6611	A2 – 132	Flare – E	V	12	78A8807.231
SD5H14 – model 6642	A2 – 132	Rotolock 1" - C	V	12	78A8807.232
SD5H14 – model 6631	A2 – 132	Rotolock 1" - M	H	12	78A8807.233
SD5H14 – model 6626	A2 – 132	OR 7/8"-3/4" - FL	V	12	78A8807.234
SD5H14 – model 6630	A2 – 132	OR 7/8"-3/4" - K	H	12	78A8807.235
SD5H14	PV7 – 119	Rotolock 1" - C	V	12	78A8807.236
SD5H14 – model 4522	PV7 – 119	Rotolock 1" - M	H	12	78A8807.237
SD5H14 – model 6629	PV7 – 119	OR 7/8"-3/4" - FL	V	12	78A8807.238
SD5H14 – model 6628	PV7 – 119	OR 7/8"-3/4" - K	H	12	78A8807.239
SD5H14 – model 4523	PV6 – 132	Rotolock 1" - M	H	12	78A8807.275
SD5H14 – model 9114	A2 – 132	Rotolock 1"	V	12	78A8807.225
SD5H14 – model 9103	A2 – 132	Flare – E	V	12	78A8807.307



78A8807.234



78A8807.232

SANDEN SD5H14 (EX SD508/510) – 24 V

Typ	Spojka – průměr mm	Připojení – typ víka	Vývody	Napětí V	Registr. číslo
SD5H14 – model 6612	A2 – 132	Flare – E	V	24	78A8807.280
SD5H14 – model 6667	A2 – 132	Rotolock 1" - C	V	24	78A8807.281
SD5H14 – model 6632	A2 – 132	Rotolock 1" - M	H	24	78A8807.282
SD5H14 – model 6627	A2 – 132	OR 7/8"-3/4" - FL	V	24	78A8807.283
SD5H14 – model 6634	A2 – 132	OR 7/8"-3/4" - K	H	24	78A8807.284
SD5H14 – model 6623	A2 – 152	Flare – BL	V	24	78A8807.240
SD5H14	A2 – 152	Rotolock 1" - M	H	24	78A8807.406
SD5H14 – model 6649	PV10	OR 7/8"-3/4" - E	V	24	78A8807.493
SD5H14 – model 9105	A2 – 132	OR 7/8"-3/4" K	V	24	78A8807.312



78A8807.283



78A8807.281