

Kompresory – ACC - COMPRESSORS R-134a LBP

Hermetické kompresory pro použití s kapilárou.

Rozsah teplot LBP -35 °C až -10 °C.

Napájecí napětí 220-240 V/50 Hz.

Typ	HP	Chladicí výkon W $T_0 -25\text{ °C}, T_k +55\text{ °C}$	Registr. číslo
GD 24 AA	1/20	34	7153000.818
GD 36 AA	1/12	61	7153000.819
GL 45 AA	1/8	81	7153000.820
GL 60 AA	1/6	106	7153000.822
GL 70 AA	1/5	120	7153000.825
GL 80 AA	1/5	144	7153000.823
GL 90 AA	1/4	164	7153000.824
GL 99 AA	1/4	174	7153000.826
GP 12 AB	1/3	190	7153000.827
GP 14 FB	3/8	228	7153000.828
GP 16 FB	3/8	266	7153000.807
GX 18 FB	1/2	395	7153000.829
GK 21 FB	5/8	488	7153000.808
GX 23 FB	5/8	605	7153000.809

U kompresorů řady X je nutné použít chlazení ventilátorem.



Kompresory – ACC - COMPRESSORS R-600a LBP

Hermetické kompresory pro použití s kapilárou.

Napětí 220-240 V/50 Hz, kompresory s vysokou účinností.

Rozsah teplot LBP -30 °C až -10 °C.

Typ	HP	Chladicí výkon W $T_0 -25\text{ °C}, T_k +55\text{ °C}$	Registr. číslo
HQY 55 AA	1/9	62	7153000.841
HQY 70 AH	1/8	80	7153000.842
HQY 80 AA	1/7	99	7153000.843
HQY 90 AH	1/6	109	7153000.844
HQY 99 AA	1/6	119	7153000.845
HPY 12 AA	1/5	144	7153000.446
HPY 14 AA	1/5	166	7153000.447
HPY 16 AA	1/4	181	7153000.448

